

Miller TurboLite Personal Fall Limiters (PFL)

THE RIGHT CONFIGURATION

with more than 75 different options, there is a Miller TurboLite perfect for the job at hand.

- Lightweight aluminum connectors reduce weight while maintaining the strength needed to support workers
- Unit and lanyard end connector combinations available for both 9-foot and 6-foot TurboLite PFLs



Unit Connectors



Steel Carabiner;
1" (25.4 mm)
Gate Opening



D-Ring Swivel Hook
3/8" (9.5 mm) Gate



Aluminum Carabiner;
3/4" (19.1 mm)
Gate Opening



Snap Hook;
3/4" (19.1 mm)
Gate Opening



Without Unit
Connector

Lanyard End Connectors



Snap Hook;
3/4" (19.1 mm)
Gate Opening



Aluminum Snap Hook;
3/4" (19.1 mm)
Gate Opening



Rebar Hook;
2-1/2" (63.5 mm)
Gate Opening



Aluminum Rebar Hook;
2-1/2" (63.5 mm)
Gate Opening



Swivel Snap Hook;
3/4" (19.1 mm)
Gate Opening



Swivel Rebar Hook;
2-1/2" (63.5 mm)
Gate Opening

MILLER TURBOLITE PERSONAL FALL LIMITER

| | UNIT CONNECTOR | LANYARD END CONNECTOR |
|---------------|--------------------|-----------------------|
| 9-FT. MODELS | | |
| MFL-12-27/9FT | Aluminum Carabiner | Aluminum Rebar Hook |

6-foot TurboLite Specifications

MATERIALS

Housing: High-impact Nylon
Webbing: Vectran core, polyester jacket 1" wide
x 0.06" thick (25.4 mm x 1.5 mm)

TECHNICAL

Maximum Working Capacity: 400 lbs (181.4 kg)
Working Length: 6 ft (1.8 m) web lifeline
Weight: 1.9 lbs (0.86 kg) (Model MFL-16-27/6FT)

CERTIFICATIONS

Meets OSHA 1926.502, 1910.66, ANSI A10.32-2012, ANSI Z359.14-2012 Class A and B, CSA Z259.2.2 Type 1 requirements

9-foot TurboLite Specifications

MATERIALS

Housing: High-impact Nylon
Webbing: Vectran core, polyester jacket 1" wide
x 0.06" thick (25.4 mm x 1.5 mm)

TECHNICAL

Maximum Working Capacity: 400 lbs (181.4 kg)
Working Length: 9 ft (2.7 m) web lifeline
Weight: 3.1 lbs (1.4 kg) (MFL-17-27/9FT)

CERTIFICATIONS

Meets OSHA 1926.502, 1910.66, ANSI A10.32-2012, ANSI Z359.14-2012 Class A and B, CSA Z259.2.2 Type 1 requirements

